INFINITY
Nanjing Infinity Technology Co.,Ltd.

No. 55 Runfa Road,Jiangning District,Nanjing,China
Tel: +86-025-52634026
Phone & WeChat: +86 13851427688 / 15618213281
Email: inf1188@vip.sina.com



Frame Core Chokes SQ3224Vertical Series

Characteristics：

- Compact Size with Low Leakage Flux due to the O-type SQ ferrite core
- Low Stray Capacitance for broad-frequency noise attenuation
- Single-Layer Winding eliminates risk of interlayer shorts
- High Normal Mode Noise Suppression
- Reduced Winding Time by up to 90%
- High Inductance achieved via proprietary ferrite mixing and sintering technology

Common Applications：

- Switching Power Supplies
- LED Drivers
- Industrial Automation
- Communication Devices
- Household Appliances
- Audio/Medical Equipment

Specifications:

- Rated Voltage: AC/DC 250V
- Operating Temperature: -40°C to +120°C
- Withstanding Voltage:
  AC 2000V for 60 sec or
  AC 2400V for 1 – 2 sec (Line-to-Line)
- Insulation Resistance: ≥100 mΩ (DC 500V)
- Temperature Rise: ≤40°C at rated current

Options：

- Bulk or Tape & Reel packaging
- Custom inductance, wire gauge, and winding configuration
- Alternative ferrite materials for tailored performance
- SMD versions available on request

Model Comparison Table


Test Condition:1KHz/0.3V AT(25 ° C)

Specifications and Electrical Characteristics

INF Code	Inductance	Wire Diameter	Turns	DC Resistance	Applicable Enameled Wire Diameter	Operating Current	Applicable Power
SQ3224-1.5mH	1.5mH	1.0*2.5	17	10mΩ MAX	1.8	15～20A	500～1800W
SQ3224-2mH	2.0mH	0.8*2.5	20	30mΩ MAX	1.6	12～16A	1000～1500W

Dimensions:[mm]

Vertical



Horizontal

In Product Development